



- ▶ Residential / Industrial luminaire
- ▶ Diffused light with IP65/IP66
- ▶ Traditional look with LED tech inside
- ▶ Short ROI (Return of Investment)
- ▶ Optional Dimming/Emergency/Corridor

Benefits

- Moisture-proof luminaire IP65/IP66s
- Excellent total cost of ownership with attractive payback times
- Long-life LEDs reduce the maintenance and product replacement costs
- Unified Glare Rating is lower or equal to fluorescent tube(UGR<19)
- Three standards available - 600 mm / 1200 mm / 1500 mm
- No annoying noises, vibrations and low flickering
- Significant sustainability due to lower energy, reduced waste and no hazardous substances such as mercury and lead
- 100% efficacy - directed light which guarantees that all the luminocity goes where is needed
- Approved for indoor use or in canopied outdoor areas

ProLight is a highly functional luminaire range that delivers great lighting quality in the face of dust, dirt and moisture. Durable, maintenance free and efficient: high-quality LED luminaires are a reliable lighting tool for keeping operating costs sustainably low. Aspects of economy have been combined with classical styling, performance and toughness for ProLight. When it comes to lighting quality, ProLight is bound to impress with excellent colour rendering up to Ra > 90 and colour temperatures from 2700 Kelvin to 6500 K. With a service life of 50,000 hours at 80 % luminous flux, ProLight is virtually maintenance free. Optionally ProLight could implement corridor function to increase the energy saving to maximum. According to the latest standards ProLight can be equipped with Emergency module with up to 4 hours stand alone time. The dimming option can also help to reduce the electricity bill. All these options make ProLight the perfect solution for even the most rigorous project.

MODEL	ProLight 60	ProLight 120	ProLight 150
Input power	20 W	40 W	50 W
Useful quantity of light	2 200 Lm	4 400 Lm	5 500 Lm
UGR	UGR 19		
Led used / pcs	Osram/Samsung		
Power supply / Pfc	230V AC/ PFC>90		
Internal thermal protection	automatic		
Working temperature	-25° to +40°C		
Environment protection	IP 65/ Optional IP 67		
Dimensions mm	600x110x100	1200x110x100	1500x110x100
Weight kg	2 kg	2.3 kg	2.6 kg
LED Lm70	50.000 h		
Application	Working halls, shops, Malls, underground parkings		

