## ROMITECH 33 LED Abbey L



- > Traditional functional streetlight
- > Extreme conditions up to -40C
- > Customasable lenses
- > High IP65 with tempered glass
- > Efficiency more than 110 Im/W

**Benefits:** 

- \* Delivers reliable performance and significant energy savings
- \* Provides a choice of high system efficacy levels to meet different energy saving targets
- \* Simple, economical, sustainable and reliable LED luminaire with low maintanance costs
- \* Ensures visual comfort for all users
- \* OPTIONS- DALI, CRI 80( typical 70);
- \* Surge protection of 6kV

Energy-efficient outdoor lighting solutions are important in every municipality, for reasons of environmental protection, light aesthetics and safety at night. Furthermore, we need solutions we can truly rely on.

Our model Abbey road-lighting luminaire brings a new quality of light to residential areas, industrial estates, local roads and cycle paths. This is the perfect combination - superior optics, a weatherproof housing and easy maintenance. This lightening fixture is suitable even for extreme conditions of up to - 40 C.

The color temperature can also be customised. Along with the high enviorment protection model Abbey comes with a build in termal protection and highly efective power supply.

MODEL	AbbeyL 60W	Abbey 80W
Input power Входяща мощност	60W	80W
Useful quantity of light Произведена светлина	7 000 Lm	9 400 Lm
Tilting	+/- 7.5 degrees	
LED used/pcs Използвани LED/бр	Osram	
Lenses Лещи	Wide and Narrow Street	
Power supply/ Pfc Захранване, КПД	198-264V AC/ PFC>90	
Internal protection Вътрешна защита	Class 1; thermal	
Working temperature Работна температура	- 40 to + 40°C	
Environment protection Външна защита	IP 65 Aluminium body with tempered glass	
Dimensions mm Размери мм	750x355x165	
Weight kg Тегло кг	6.8 kg	
LED LM70	100,000 h	

Ldt files are downloadable free at www.rommtech-3s.com/en/led-lighting,