



- ▶ Office lighting
- ▶ Suitable for glare control
- ▶ Glare-free emission $L < 1000 \text{ cd/m}^2$ at $60^\circ/65^\circ$
- ▶ Good ROI (Return of Investment)
- ▶ Dimming and Emergency available

Benefits

- Unified Glare Rating is lower than fluorescent tube(UGR<19)
- Provides a choice of high system efficacy levels to meet different energy saving targets
- Applications are surface mounted, recessed or pendant
- DALI dimming and Emergency mode available
- Long-life LEDs reduce the maintenance and product replacement costs



LUPO is a **LED Uniform Panel for Offices**.

Designed with innovative technologies to provide always perfect, glare-free light.

At the same time, it is efficient and flexible: qualities by which the new generation stands out as contemporary office lighting system that provides perfect lighting conditions for many situations.

The family provides interior solutions in three efficiency levels - high efficiency, high output and standard. Available as 40W delivering up to 5200Lm and 60W with 7200Lm.

They can be build as surface mounted, pendant or recessed.

LUPO is standarty produced with dimmensions 600mm/600mm but can be customised to the conventional sizes - 300mm/300mm, 300mm/1200mm, 300mm/1500mm, 600mm/1200mm. Standard CRI is 80 but can reach to 95 on request. With color temperature from 3000K to 6000K.

Due to the high uniformity of the emitted light and the low overall brightness, the luminaire is applicable where the unified glare rating is of importance: schools, offices, hospitals, workinghalls.

MODEL	LUPO 30 W	LUPO 42 W
Input power	30 W	42 W
Useful quantity of light	4 200 Lm	5 700 Lm
UGR	UGR<19	
Power supply / Pfc	230V AC/ PFC>90	
Internal thermal protection	automatic	
Working temperature	-25° to +40°C	
Environment protection	IP 20	
Dimensions mm	595x595x50	
Weight kg	4 kg	
LED Lm80	50.000 h	
Application	Indoor for offices, schools, hospitals	

